Optional Items











Water Chiller

Air Extraction System

Supporting Pin Kit

All Extraction System		Supporting Fill All				
Specification		T500				
Laser Wattage		60W	80W	100W	150W	200W
Laser Source		Sealed CO ₂ Laser				
Cooling		Air-cooled		Water-cooled		
Working Area		51 x 35 in. (1300 x 905 mm)				
Max. Part Size (W x L x H)	w/o cutting table	53 x 36 x 5 in. (1346 x 916 x 127 mm) with 2"/4" lens				
	All doors open	53 x ∞ x 1 in. (1346 x ∞ x 25 mm) with 2"/4" lens				
	With cutting table	52 x 35 x 4.4 in. (1325 x 889 x 114 mm) with 2"/4" lens				
		52 x 35 x 1.5 in. (1325 x 889 x 38 mm) with 6" lens				
Dimensions		71.6 x 49.2 x 52.3 in. (1820 x 1250 x 1330 mm)				
Weight		420 kg / 924 lb		440 kg / 968 lb		
Driver		AC Servo Control				
Maximum Cutting Speed*		40IPS				
Throughput (SIPH-Square Inch Per Hour)		133.95 in2/hr (864.2 cm2/hr)				
Speed Control		Adjustable from 0.1 - 100% (Up to 16 color-linked speed settings per job)				
Power Control		Adjustable from 0 - 100% (Up to 16 color-linked power settings per job)				
Engraving Capability		256-level gray scale image processing capability				
Distance Accuracy		0.254 mm or 0.1% of move, whichever is greater				
Z-Axis Movement		Manual				
Resolution (DPI)		Available 125, 250, 300, 500, 600, 1000				
Computer Interface		10 Base-T Ethernet, Full speed 2.0 USB				
Focus Lens		Standard 4" focal lens in enclosed lens carriage (Optional 2"/ 6" lens)		Standard 6" focal lens in enclose lens carriage(Optional 2"/ 4" lens		
Display Panel		4-line LCD panel showing current file name, total working time, laser power, engraving speed, file(s) loaded into memory buffer, setup and diagnostic menus.				
Safety		Class I Laser Product Compliant with EN60825 Class II Laser Product Compliant with CDRH 2006/42/EC Machinery Directive Compliance				
Cutting Table		Knife-shaped cutting bars with aluminum grid cutting table				
Operation Vottage		200-240VAC. 50/60Hz auto switching, Max.15A		200-240VAC. 50/60Hz auto switching, Max. 25A		200-240VAC. 50/60Hz auto switching, Max. 30A
Air Exhaust System		External exhaust system required to connect to 8-inch and 1-inch openings on machine				

^{*} Speed does not equal to throughput. See dealer or visit www.GCCworld.com for more details. △ Specifications are subject to change without prior notice.









Authorized Dealer













GCC Headquarters 4F-1., No.236, Fude 2nd Rd., Xizhi Dist., New Taipei City 22151, Taiwan 886-2-6616-6692 Fax: 886-2-2694-6875 No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China 86-512-5726-1515 Fax: 86-512-5726-1518 GCC Europe B.V. Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands 31-10-458-9367 Fax: 31-10-451-9874 GCC America, Inc 323 Paseo Tesoro, Walnut, CA 91789, USA

1-909-718-0248 Fax:1-909-718-0251 US & Canada Only Toll Free: 1-888-284-5211

Laser Cutter

GGG LaserPro 1500

The Fastest Large Format Laser Engraving and **Cutting System in Its Class**



- High wattage laser tube is available
- Cutting and engraving in one machine
- AC Servo Motor Technology for precise movement control
- Adjustable acceleration enables higher productivity
- Laser Pulsing Technology for accurate laser firing control
- Excellent engraving quality with 3D capacity
- AAS Module performs automatic graphic contour tracking task
- Rigid welded steel chassis





Laser Cutter

GCC LaserPro T500

Lase

AC Servo Motor Motion

A motor of high torque, high speed and high caliber works perfectly with the high demands of LaserPro T500. The state of the art in AC Servo Motor design assures long motor lifetime and high precision.




LaserPro

Outstanding Cutting Capability

T500 delivers high cutting quality with LaserPro's unique laser firing control technology. Up to 200W output power options, GCC LaserPro T500 can cut through 1" (25 mm) acrylic in a single pass with a smooth finish and unmatched clear cutting edge.

Excellent Speedy Scribing Quality

T-500 embrace extraordinary control system and rigid motion system allow user to create top-notch vector scribing quality with high speed.





Superior Engraving Quality

T500 persists with GCC LaserPro's excellent engraving capability. Having cutting and engraving capability in one product, no more time wasted on switching materials from cutting and engraving machine. Compare to conventional cutting product. It is difficult to have a good and consistent raster performance with large working area, but T500 can.

AAS Contour Cutting Device (Patented) (Optional)

Developed by LaserPro, AAS is an exceptionally user-friendly operation which offers accurate and faultless contour cutting by automatically tracking the position of graphics.






Knife-shaped Cutting Table

Unique cutting table with tipped bars that can be easily adjusted without tools to create different levels of working depths. The cutting table of T500 reduces laser reflections and delivers clear cutting edge.

SmartPOINT Positioning Device (Patented)

Material positioning made extremely easy by use of 4 red beam diodes. Simply aim each red beam diodes at distinct points on the material and the red beam becomes a very useful positioning tool to replicate previous jobs precisely.





LED Light Illumination System

A LED light module that illuminates the working space and makes every engraving detail easy to see.



system for your choice.

GCC LaserPro T500

Developed on the basis of GCC LaserPro's accumulated technology